

Brolac Silver

Brolac Silver is a single pack 'ready to use' Aluminium Paint. Based on a synthetic medium, it incorporates flake Aluminium with a high leafing quality producing a smooth film with more uniform colour. Recommended for both interior and exterior surfaces, it can be applied on storage tanks, pipelines, rolling shutter etc as well.

PRODUCT BENEFITS



- Maximum Colour and Gloss Retention
- Good Hiding and Coverage
- Better Durability




PRODUCT FEATURES

AVAILABLE PACK SIZES



500 ml 1 Ltr 4 Ltrs 20 Ltrs

APPLICATION



COVERAGE



235 - 250 sq. ft / litre. at
12 - 14 micron DFT

*Actual coverage may vary due to factors such as method and condition of application, surface roughness and porosity and weather conditions.

RECOMMENDED USE

Metal Surfaces: In all interior & exterior metal surfaces after proper surface preparation.

Wood Surfaces: Also applicable on wooden surfaces.



SURFACE DRYING TIME



Technical Data:

Finish	: Bright, Lustrous & Smooth.
Colour options	: Silver Finish
Flow and Leveling	: Satisfactory
Consistency	: Smooth & Uniform
Flexibility & Adhesion	: Excellent
Corrosion Resistance	: Excellent
Surface Dry time	: 3 hrs* (30° C / 50% RH)
Over coating period	: 16 hrs* (30° C / 50% RH)
No. of coats specified	: 1 coat
Recommended Dilution	: Brush: Ready for Use. Thinning not required Spray: 5% by volume with J&N GP Thinner

*Recoat and drying period may vary under different conditions



HOW TO PREPARE (SURFACE / WALL)

SURFACE PREPARATION:

Cleaning: Free the surface from grease, rust, moisture, loose particles and peeling/flaking paint by sanding with Emery Paper 180.

Steel surfaces should be manually prepared through power or hand tool. New galvanized and Aluminium surfaces should be cleaned and de-greased, followed by pre-treatment with an appropriate pre-treatment primer to ensure good adhesion.

HOW TO APPLY ?

PRIMER:

Ferrous Metal Surface: Apply 1 - 2 coats of J&N Super Red Oxide Primer on the metal surface by thinning (if necessary) with J&N GP Thinner. Allow drying for 8 - 10 hrs after each coat.

Non-Ferrous Metal Surface: Apply 1 - 2 coat of Zinc Chrome Yellow Primer on the metal surface by thinning (if necessary) with J&N GP Thinner. Allow drying for 8 hrs.

Wooden Surface: Apply first coat of J&N Pink / White Primer on the wooden surface by thinning (if necessary) with J&N GP Thinner. Allow drying for 5 - 6 hrs. Use any synthetic Putty to fill minor cracks, dents or holes. After drying sand the surface with Emery Paper 180. Apply another coat of J&N Pink / White Primer. Allow drying for 5 - 6 hrs.

Galvanized iron: Apply a coat of Etch primer before application of Brolac Silver.

Application (Topcoat):

Apply single coat of Brolac Silver after thorough stirring. Allow it to dry for 16 hrs.

Post Application Instructions: To remove stains, sponge clean with a mild soap solution and wipe clean. Before cleaning, please ensure a drying time of one week.

Storage and Transportation:

- Store the containers at constant temperatures, away from direct sunlight /elevated temperatures.
- Keep the product in frost-free environment.
- Store the containers in upright position to avoid leakage or damage.
- Do not pour the waste paint in drains or other water sources.

Shelf Life: 2 years from the date of manufacture in the original tightly closed containers, stored away from direct sunlight and excessive heat.

Pack Size: Available in 500ml, 1L, 4L and 20L packs.

PRECAUTIONS

- Keep containers upright, tightly closed in a cool, dry, well ventilated place.
- Ensure opened containers are tightly closed, when not in use.
- Store away from excessive heat, direct sunlight and other flammable materials.
- Flammable product, store in a place away from direct sunlight, heat and sparks.
- Keep out of reach of children and pets.
- Do not store near food, drinks or animal feed.
- Do not mix with incompatible materials.
- Use personal protective equipment like goggles, face masks and gloves.
- Ensure good ventilation during application and drying.
- Do not inhale the vapour or spray.
- In case of contact with eyes or skin, wash immediately using plenty of water. Seek medical advice, if irritation persists.
- In case of ingestion, seek immediate medical attention.
- Do not dispose any spilled or unused paint in drain, water bodies and landfill.
- Dispose spillages or unused paint and containers, through appropriate disposal agency.
- This product does not have any added Lead, Cadmium, Mercury & Chromium.

For product related queries, feedback and quality complaints, Please contact:

Customer care: +91 8300 03 04 04

E-mail: ccc@sheenlac.in,

Visit us: www.jnpl.in

Regd. Office: Jenson & Nicholson Paints Private Ltd.

(A joint venture of Jenson & Nicholson India Ltd and Sheenlac Paints Ltd)

Old No. 109B, New No. 124, Developed Plots, SIDCO Industrial Estate, Ambattur, Chennai - 600 098. Tamil Nadu, INDIA.

All information mentioned in this data sheet are based on tests conducted in laboratory conditions. Results may vary depending upon atmospheric conditions, application methodologies and substrates. We reserve the right to alter the given data without notice.

Ver.2.0 / TDS / 2020