

## Jensolin Acrylic Wall Putty

Jensolin Acrylic Wall Putty, a ready-to-use water-based putty lends a very strong and durable foundation to masonry walls.

### PRODUCT BENEFITS



- Excellent Filling, Levelling & Sanding Properties
- Exceptional Ease-of-Application
- Water Resistant
- Smooth & Hard Finish
- Quick & Easy Repair
- Quick Drying
- Strong & Adhesive Bonding
- High Durability



### PRODUCT FEATURES

#### AVAILABLE PACK SIZES



1 Kg

5 Kg

10 Kg

20 Kg

#### COVERAGE



35-45\* sq. ft. / Kg for single coat (by putty knife) finish under normal conditions

\*Actual coverage may vary due to factors such as method and condition of application, surface roughness and porosity and weather conditions.

### RECOMMENDED USE

Jensolin Acrylic Wall Putty is recommended to be used on interior cement plasters, ceilings, asbestos sheets, concrete, etc.



### SURFACE DRYING TIME



### Technical Data:

Colour	:	White
Gloss / Sheen	:	Matt
Recommended Dilution	:	Ready to use
Surface Dry time	:	30 minutes* (25°C / 50% RH)
Over coating period	:	4 - 6 hrs* (25°C / 50% RH)

\*Recoat and drying period may vary under different conditions



## HOW TO PREPARE (SURFACE / WALL)

### Cleaning:

- Ensure that the surface is free from dust, dirt, chalking, oil, grease, loosely bound particles or any other contamination.
- Ensure removal of Algae and Fungal growth, if any using wire brushing and bio wash solution.
- Sand the glossy surface using Emery Paper 180, as it results in a roughened surface for good adhesion of the primer to the surface.
- Apply one coat of Jenson & Nicholson Water Thinnable Interior Primer at the recommended dilution level, using standard brush application. Let it dry for minimum 3-4 hours. Using Emery Paper 180, sand the surface lightly. Wipe clean.



**New concrete, masonry or plaster:** Allow the newly constructed cement surface to cure for minimum of 30 days, prior to application of Jenson & Nicholson Acrylic Base Water Thinnable Cement Primer. Ensure that the wall to be painted is completely dry and free from any cement residue.

### HOW TO APPLY ?

- Apply one coat of Jenson Acrylic Wall Putty using Putty Knife. Smooth the surface by filling dents, holes and imperfections. Allow it to dry for 4-6 hrs.
- Apply a second layer of putty, if required. Allow Putty to dry thoroughly, preferably overnight.
- Sand the surface with fine Emery Paper and wipe clean to get a leveled surface.
- Apply topcoat on the finished surface, after application of another coat of primer.

### Storage and Transportation:

- Store the containers at constant temperatures, away from direct sunlight /elevated temperatures.
- Keep the product in frost-free environment.
- Store the containers in upright position to avoid leakage or damage.
- Do not pour the waste paint in drains or other water sources.

### Shelf Life:

2 years from the date of manufacture in the original tightly closed containers, stored away from direct sunlight and excessive heat.

### Pack Size:

Available in 1 kg, 5kg, 10kg and 20 kg packs.

### Application precautions:

- Proper Consistency of putty is very important.
- Do not dilute the product above the suggested dilution levels.
- Do not rub putty surface harshly with rough Emery Paper, to avoid breaking of the protective film.
- Ensure application of putty only on fully cured surfaces.

### WHAT ARE THE PRECAUTIONS ?

- Keep containers upright, tightly closed in a cool, dry, well ventilated place.
- Ensure opened containers are tightly closed, when not in use.
- Store away from excessive heat, direct sunlight and other flammable materials.
- Highly Flammable product so, store in place away from heat and sparks and No smoking to be allowed near the product.
- Keep out of reach of children and pets.
- Do not store near food, drinks or animal feed.
- Do not mix with incompatible materials.
- Use personal protective equipment like goggles, face masks and gloves.
- Ensure good ventilation during application and drying.
- Do not inhale the vapour or spray.
- In case of contact with eyes or skin, wash immediately using plenty of water. Seek medical advice, if irritation persists.
- In case of ingestion, seek immediate medical attention and do not induce vomiting.
- Do not dispose any spilled or unused paint in drain, water bodies and landfill.
- Dispose spillages or unused paint and containers, through appropriate disposal agency.

### For product related queries, feedback and quality complaints, Please contact:

Customer care: +91 8300 03 05 05

E-mail: [ccc@jnpl.in](mailto:ccc@jnpl.in),

Visit us: [www.jnpl.in](http://www.jnpl.in)

Regd. Office: Jenson & Nicholson Paints Private Ltd.

Old No. 109B, New No. 124, Developed Plots, SIDCO Industrial Estate, Ambattur, Chennai - 600 098. Tamil Nadu, INDIA.

All information mentioned in this data sheet are based on tests conducted in laboratory conditions. Results may vary depending upon atmospheric conditions, application methodologies and substrates. We reserve the right to alter the given data without notice.

Ver:2.0 / TDS / 2020



WOOD COATINGS