

## JN Universal Cement Primer

Jenson & Nicholson Universal Cement Primer, a white coloured primer is exclusively designed for application on interior and exterior walls made of sand, cement plaster, asbestos, bricks, etc. The product covers stains and discolourations. Moreover, it hides surface marks and darker colours.

### PRODUCT BENEFITS



- Ideal for both Interior & Exterior Surfaces
- Excellent Opacity & Whiteness
- Good flow & Ease-of-application
- Excellent Coverage ensuring improved aesthetics of top coats



### PRODUCT FEATURES

#### AVAILABLE PACK SIZES



#### COVERAGE



100-150\* sq. ft. / Litre for one coat finish under normal conditions

\*Actual coverage may vary due to factors such as method and condition of application, surface roughness and porosity and weather conditions.

### RECOMMENDED USE

Jenson & Nicholson Universal Cement Primer is recommended for all types of interior and exterior plastered surfaces, brick works, asbestos sheets, concrete, etc.



### SURFACE DRYING TIME



#### Technical Data:

Colour	: White
Gloss / Sheen	: Matt
Recommended Dilution	: Up to 1:1 mixing with portable water, depending on the application consistency required.
Surface Dry time	: 30 minutes* (25°C / 50% RH)
Over coating period	: 4 - 5 hrs* (25°C / 50% RH)
Stability of thinned paint	: Use within 24 hours

\*Recoat and drying period may vary under different conditions



## HOW TO PREPARE (SURFACE / WALL)

### Surface Preparation:

- Ensure that the surface is free from dust, dirt, grease, loosely bound particles or any flaking material.
- Ensure removal of Algae and Fungal growth, if any, using wire brushing and clean it with water.
- Sand the glossy surface using Emery Paper 180, as it results in a roughened surface for good adhesion of the primer to the surface.



### HOW TO APPLY ?

Apply one coat of J&N Universal Cement Primer by diluting it with potable water, at recommended ratio. Let it dry for 4-5 hrs. If required, apply one more coat of J&N Universal Cement Primer.

### Recommended Dilution Ratio:

Up to 1:1 mixing with potable water is recommended, depending on the application consistency required.

### Application precautions:

- Do not dilute the product above the suggested dilution levels.
- Stir the product properly, before use.
- Seal the container, when not in use.

### Post application care:

Ensure proper washing and cleaning of all dust, Algal and Fungal growth at regular intervals of 5-6 months, for longer durability and better retention of aesthetics.

### For product related queries, feedback and quality complaints, Please contact:

Customer care: +91 8300 03 04 04

E-mail: [ccc@sheenlac.in](mailto:ccc@sheenlac.in),

Visit us: [www.jnpl.in](http://www.jnpl.in)

Regd. Office: Jenson & Nicholson Paints Private Ltd.

(A joint venture of Jenson & Nicholson India Ltd and Sheenlac Paints Ltd)

Old No. 109B, New No. 124, Developed Plots, SIDCO Industrial Estate, Ambattur, Chennai - 600 098. Tamil Nadu, INDIA.

All information mentioned in this data sheet are based on tests conducted in laboratory conditions. Results may vary depending upon atmospheric conditions, application methodologies and substrates. We reserve the right to alter the given data without notice.

TDS / 2022 / Ver.1.0



### Storage and Transportation:

- Do not store or transport the containers under direct sunlight / elevated temperatures.
- Store the containers in upright position to avoid leakage or damage.

### Shelf Life:

Two years from the date of manufacture in the original tightly closed containers, stored away from direct sunlight and excessive heat.

### Pack Size:

Available in 1L , 4L , 10L and 20L packs.

### PRECAUTIONS

- Keep containers upright, tightly closed in a cool, dry, well ventilated place.
- Ensure opened containers are tightly closed, when not in use.
- Store away from excessive heat, direct sunlight and other flammable materials.
- Keep out of reach of children and pets.
- Do not store near food, drinks or animal feed.
- Do not mix with incompatible materials.
- Use personal protective equipment like goggles, face masks and gloves.
- Ensure good ventilation during application and drying.
- Do not inhale the vapour or spray.
- In case of contact with eyes or skin, wash immediately using plenty of water. Seek medical advice, if irritation persists.
- In case of ingestion, seek immediate medical attention.
- Do not dispose any spilled or unused paint in drain, water bodies and landfill.
- Dispose spillages or unused paint and containers, through appropriate disposal agency.
- This product does not have any added Lead, Cadmium, Mercury & Chromium.